

<i>Name of the document</i> Declaration of confirmity Wooden panels of spruce or pine, untreated $\geq 12\text{mm}$	<i>Document nr</i> CPR150	<i>Page</i> 1 of 2
<i>Prepared by</i> Michaela Pfeiffer	<i>Number of edition</i> 1	
<i>Approved by</i> Lars Kristen Holst	<i>Replaces edition</i> -	<i>Date of edition</i> 2022-10-28

DECLARATION OF CONFIRMITY – CPR150

1. Product group and identification

Sawn, planed or profiled wooden panels of spruce or pine with or without tongue, untreated with a minimum thickness of 12mm/8mm.

2. Product information

Sawn, planed or profiled wooden panels with or without battens, untreated, which meet the requirements of EN 14915.

For additional or more detailed information about the delivered product, in addition to what is stated below, see the package specification and any attached commercial document.

3. The intended use of the product

Wooden panel for walls and ceilings which can be used indoors as well as outdoors.

4. Manufacturer

Company: [Moelven Wood AB](#)
Address: [Box 6008, 650 08 Karlstad, Sweden](#)
Telephone: [+46 10 122 50 50](#)
E-mail: order.woodab@moelven.se
Webbsite: www.moelven.com

5. System for assessment and continuous control of the construction product's performance

System 4 in AVCP.

Production consists of standardized products with well-known and constant properties. In order to ensure that the performance of the products complies with the values declared below, we have a quality control system. In order to meet the requirements, no type testing is normally required. If, for example, a different type of wood is to be used or if the product is to receive a new type of treatment, the declaration must be reviewed. No certification body required for assessment system 4.

6. Certification and stated performance

Performance for sawn, planed or profiled wooden panels with or without battens (not treated with wood protection or fire protection) in accordance with the harmonized European standard EN 14915:2013 Wooden panels - Properties, testing and control and marking.

The specified standard that is followed has no replacement standard for the UK, but also applies to complying with the UKCA.



<i>Name of the document</i> Declaration of confirmity Wooden panels of spruce or pine, untreated ≥12mm	<i>Document nr</i> CPR150	<i>Page</i> 2 of 2
<i>Prepared by</i> Michaela Pfeiffer	<i>Number of edition</i> 1	
<i>Approved by</i> Lars Kristen Holst	<i>Replaces edition</i> -	<i>Date of edition</i> 2022-10-28


7. Declared performance

Essential characteristics	Declared values
Reaction to fire	PCAB: D-s1,d0 , PNSY: D-s2,d0 (according to EN 13501-1)
Application	I – Internal and E – External (according to TS 15912)
Intened area of use	W – Walls and C - ceilings
Wood species	PCAB (spruce) or PNSY (pine)
Durability	4 (according to EN 350-2)
Density	PCAB: 440 kg/m ³ , PNSY: 480 kg/m ³
Sound absorption	0,1/0,3 (according to EN 14915)
Release of formaldehyde	E1
Content of pentachlorophenol	NPD (no performance detected)
Hazardous substances	NPD (no performance detected)
Resistant to fixing	NPD (no performance detected)

8. Additional technical documentation

The property of the product declared in section no.1 and 2 is in accordance with the property stated in section no.7. This declaration of performance is prepared under the responsibility of the manufacturer specified in Section No. 4.

Karlstad, 2022-10-28
Lars Kristen Holst, manager product management



.....
(signature)